



SATURN ENERGY AUDITOR FIELD GUIDE



SATURN RESOURCE MANAGEMENT

Serving the building performance industry since 1980

1.800.735.0577 • SRMI.BIZ



Saturn Energy Auditor Field Guide

Produced by John Krigger and Chris Dorsi

Illustrated by John Krigger, Bob Starkey,
Steve Hogan, and Mike Kindsfater

This edition compiled by Darrel Tenter

The *Saturn Energy Auditor Field Guide*
describes the procedures used to analyze the
performance of existing homes.

The companion volumes
Saturn HVAC Systems Field Guide and
Saturn Hydronic Systems Field Guide
include procedures for inspecting, servicing, and improving the
efficiency and safety of residential heating and cooling systems.

The companion volume *Saturn Building Shell Field Guide*
outlines procedures for improving the effectiveness of insulation,
doors, windows, and air-sealing details.

In compiling this publication, the authors have benefited from the experience of
many individuals who have reviewed our documents, related their experiences,
or published information from which we've gained insight. Though we can't name
everyone to whom we're indebted, we acknowledge the specific contributions of
the following people: Martha Benewicz, Michael Blasnik, Anthony Cox, Bob Davis,
Jim Davis, R.W. Davis, Rob de Kieffer, Rick Karg, Rudy Leatherman, Dave Like,
Bruce Manclark, David Miller, Rich Moore, Gary Nelson, Russ Rudy, Russ Shaber,
Cal Steiner, Ken Tohinaka, John Tooley, Bill Van Der Meer, and Doug Walter. We
take full responsibility, however, for the content and use of this publication.

Copyright 2009 by

Saturn Resource Management, Inc.

Bookstore: www.srmi.biz

Online Training: www.SaturnOnline.biz

Printed in the U.S.

ISBN 978-1-880120-17-0

Ver. 070109



SATURN
RESOURCE MANAGEMENT

Foreword

The *Saturn Energy Auditor Field Guide* outlines a set of best practices for home performance organizations. This guide looks at residential structures through the eyes of the auditor who focuses on energy auditing, sales, and quality control.

Chapter 1 describes a methodical audit procedure that helps assure consistent data collection. It includes simple recommendations the auditor can make to help improve the efficiency of their customer's home right away.

Chapter 2 focuses on inspection of the home's insulation and the associated parts of the building shell. It includes tips on assessing hidden areas.

Chapter 3 describes the diagnostic procedures used to evaluate air leakage through the building shell. These procedures help the auditor determine which air-sealing measures will be most beneficial.

Chapter 4 covers the analysis of heating and cooling systems. These procedures are used to specify maintenance, assess the cost effectiveness of system upgrades, and protect the health and safety of the occupants.

Chapter 5 describes the analysis of baseload consumption, including water heating, refrigeration, and lighting. These simple procedures often identify the best energy-saving procedures of all.

Chapter 6 identifies the best ways to improve doors and windows. Though the energy savings from window and replacement are often minimal, these upgrades remain among the most popular home improvements.

Chapter 7 focuses on the well being of both auditors and customers. Health and safety remains paramount to our work in the building trades, and we hope you take to heart the advice contained here.

Chapter 8 includes inspection procedures for mobile homes. Some of these measures can pay off handsomely, especially for the owners of older homes.

The *Saturn Field Guides* have benefited greatly over the years from the generous feedback of our readers. Please help continue this process by sending us your comments and suggestions.

John Krigger
jkrigger@srmibiz

Chris Dorsi
cdorsi@srmibiz

TABLE OF CONTENTS

1: Energy Audits and Customer Relations

What is an Energy Audit?	15
Purposes of an Energy Audit	15
The Energy Auditing Process	16
Screening and Surveys	17
Visual Inspection	18
Diagnostic Testing	22
Numerical Analysis	23
Understanding Energy Usage	24
Baseload Versus Seasonal Use	24
Energy Indexes	29
Electricity Peak Load	31
Carbon Footprint	32
The Work Scope and Contracts	33
The Work Scope	33
Contracts	34
Work Inspections	35
In-Progress Inspections	35
Final Inspections	35
Quality Control Versus Quality Assurance	36
Energy-Auditing Disclosure and Ethics	37
Customer Relations	37
Communication Best Practices	38
Customer Interview	39
Sales Best Practices	40
Customer Education	40
Reducing Heating Consumption	40
Reducing Hot Water and Laundry Consumption	42
Reducing Cooling Consumption	43

2: Evaluating Insulation

Infrared Scanning	48
Evaluating Attic or Roof Insulation	48
Attic Ventilation	49
Attics in Story-and-a-Half Homes.....	50
Evaluating Closed Roof Cavities.....	53
Walk-Up Stairways and Doors	54
Retractable Attic Stairways.....	55
Evaluating Wall Insulation	55
Thermal Boundary Decisions.....	57
Determining Floor or Foundation Insulation.....	59

3: Diagnosing Shell and Duct Air Leakage

Air-Leakage Problems and Solutions	61
Driving Forces for Air Leakage	61
Safety Considerations for Air Sealing.....	63
Goals of Air-Leakage Testing.....	63
Air Sealing: Three Approaches	64
Air-Leakage Testing	65
Blower-Door Testing	66
Preparing for a Blower Door Test.....	68
Blower Door Test Procedures	70
Approximate Leakage Area	72
Evaluating Ventilation Level	73
Discovering Air-Leakage Trouble Spots.....	73

Air-Barrier Zone Pressure Diagnosis	77
When to Use Zone Pressure Diagnostics.....	78
Benefits of Zone Pressure Diagnostics.....	78
Primary Versus Secondary Air Barriers	79
Simple Zone Pressure Tests	80
Using a Digital Manometer to Test Air Barriers.....	82
Add-a-Hole Zone-Leakage Measurement.....	85
Locating the Thermal Boundary.....	92

4: Evaluating Heating and Cooling Systems

Heating System Replacement	95
Combustion Furnace Replacement.....	96
Combustion Boiler Replacement.....	97
Gas-Fired Heating Installation.....	100
Oil-Fired Heating Installation	100
Gas Space-Heater Replacement.....	102
Space-Heater Operation	103
Un-vented Space Heaters.....	103
Testing Gas Furnaces and Boilers.....	103
Furnace Efficiency Testing	105
Critical Furnace-Testing Parameters	112
Measuring BTU Input on Natural Gas Appliances	113
Inspecting Gas Combustion Systems	116
Oil-Burner Safety and Efficiency Service	118
Oil-Burner Inspection.....	118
Oil-Burner Testing	119
Oil-Burner Adjustment.....	122
Oil-Burner Maintenance and Visual Checks	123
Wood Stoves	123
Wood Stove Clearances.....	123
Stove Clearances	124
Wood Stove Inspection.....	125
Draft, Venting, and Combustion Air	126

Essential Combustion Safety Tests	127
Leak-Testing Gas Piping	128
Carbon Monoxide (CO) Testing	128
Worst-Case Testing for Atmospheric Venting Systems	129
Worst-Case Depressurization, Spillage, and CO	130
Improving Inadequate Draft	133
Zone Isolation Testing for Atmospherically Vented Appliances	135
Inspecting Venting Systems.....	136
Vent Connectors	136
Chimneys	139
Masonry Chimneys	139
Manufactured Chimneys.....	141
Chimney Terminations	141
Metal Liners for Masonry Chimneys	142
Special Venting Considerations for Gas.....	144
Venting Fan-Assisted Furnaces and Boilers	144
Combustion Air	146
Ducted Air Distribution	150
Evaluating Forced-Air System Airflow	151
Evaluating Furnace Performance.....	155
Measuring Airflow.....	157
Troubleshooting Airflow Problems.....	164
Improving Duct Airflow.....	169
Evaluating Duct Air Leakage	171
Troubleshooting Duct Leakage	172
Measuring House Pressure Caused by Duct Leakage..	176
Duct Air-Tightness Standards	177
Measuring Duct Air Leakage with a Duct Blower.....	178
Typical Duct Leak Locations	181
Duct Insulation	185
Hot-Water Space-Heating Distribution	186
Boiler Efficiency and Maintenance	186
Distribution System Improvements	187

Steam Heating and Distribution.....	190
Steam System Maintenance	192
Steam System Energy Conservation.....	192
Programmable Thermostats	194
Electric Heat.....	194
Electric Baseboard Heat.....	195
Electric Furnaces	196
Electric Radiant Heat	197
Central Heat-Pump Energy Efficiency	197
Room Heat Pumps	199
Evaluating Central Air-Conditioning Systems	200
Central Air-Conditioner Inspection.....	201
Air-Conditioner Sizing	203
Duct Leakage and System Airflow.....	203
Air-Conditioner Charge Checking	204

5: Baseload Measures

Water-Heating Energy Savings.....	205
Determining the Water Heater’s Insulation Level	205
Water Heater Blankets.....	206
Measuring and Adjusting Hot Water Temperature	207
Water-Heater Pipe Insulation	208
Water-Saving Shower Heads.....	209
Water-Heater Replacement	210
Gas Storage Water Heaters.....	210
Water-Heater Replacement Decisions	212
Tankless Gas Water Heaters.....	213
Solar Hot-Water System Design	214
Refrigerator Evaluation	216
Refrigerator Metering Protocol.....	217
Lighting Improvements.....	220

6: Windows, Doors, and Exterior Insulation

Window Shading	223
Exterior Window Shading Treatments	224
Interior Window Shading Treatments	224
Landscaping for Shade	225
Exterior Storm Windows	226
Double Windows	227
Window and Door Repair	227
Window Repair and Weatherstrip	228
Door Repair and Weatherstrip	228
Window Replacement	231
Replacement Window Specifications	232
Window-Replacement Options	232
Window Safety	235
Exterior Insulation, Siding, and Windows	237

7: Health and Safety

Pollutant Source Control	239
Carbon Monoxide (CO)	240
Gas Range and Oven Safety	241
Smoke and Carbon Monoxide Alarms	242
Moisture Problems	244
Crawl Space Moisture Control	247
Lead-Safe Weatherization	249
Electrical Safety	250
Evaluating Home Ventilation	251
Control of Pollutants	252
ASHRAE 62-1989: Minimum Ventilation Requirement (MVR)	253
ASHRAE 62.2 – 2007 Ventilation Standard	255
Whole-House Ventilation Systems	257

8: Evaluating Mobile Homes

Mobile Home General Auditing Tasks	264
Health and Safety	264
Repair Work	265
Evaluating Mobile Home Insulation	266
Evaluating Belly Insulation	267
Evaluating Sidewall Insulation	269
Specifying Furnace Replacement	270
Evaluating Duct Air Leakage	270
Belly Return Air Systems	272
Belly Pressure Test	273
Evaluating Shell Air Leakage	274
Air-Leakage Locations	274
Specifying Water-Heater Replacement	275
Evaluating Interior Storm Windows	276
Considering Window Replacement	277
Door Replacement Specifications	278

Appendices **279**

Required Diagnostic Equipment	279
R-values for Common Materials	280
Calculating Attic Insulation	281
Calculating Wall Insulation	285
Calculating Mobile Home Insulation	288
Refrigerator Dating Chart	290
Tables and Illustrations	291
Index	299

CHAPTER 1: ENERGY AUDITS AND CUSTOMER RELATIONS


This chapter outlines the services delivered during an energy audit. It also discusses ethics, customer relations, and customer education.

1.1 WHAT IS AN ENERGY AUDIT?

An energy audit is a package of services that delivers these benefits to customers.

Help customers make decisions about how to conserve energy and save money.

- Help customers increase the comfort, health, safety, and durability of their homes.
- Protect the environment by reducing waste and pollution.



1.1.1 Purposes of an Energy Audit

An energy audit includes some or all of the following tasks, depending on the level of the audit.

- ✓ Encourage behavioral changes that reduce energy waste.
- ✓ Inspect the building and its mechanical systems to gather the information necessary for decision-making.
- ✓ Evaluate the current energy consumption and current condition of the building.

- ✓ Diagnose areas of energy waste, health and safety, or durability problems related to energy conservation.
- ✓ Recommend energy conservation retrofits.
- ✓ Project savings expected from energy retrofits.
- ✓ Estimate labor and materials costs for energy retrofits.
- ✓ Note current and potential health and safety problems and how they may be affected by proposed changes.
- ✓ Educating the homeowner about energy usage and conservation options.
- ✓ Provide a written record of the energy audit and the recommendations offered.


Why We Care about Health, Safety, and Durability

The health and safety of customers must never be compromised by energy auditing or energy conservation measures. Harm caused by our efforts would hurt both our customers and our profession. Energy conservation work can alter the operation of heating and cooling systems, alter the moisture balance within the home, and reduce a home's natural ventilation rate. Energy auditors and technicians must take all possible precautions to avoid harm and instead deliver enhanced safety, indoor air quality, and home durability.

1.2 THE ENERGY AUDITING PROCESS

Visual inspection, diagnostic testing, and numerical analysis are the three broad types of services that compose energy audits. Screening is also an important energy-audit function, which gathers preliminary information that helps to target further energy auditing. The number of energy-auditing services and their complexity depends on the customer's commitment, the auditor's capabilities, and the requirements of energy programs among other factors. Here, we classify energy audits as Levels 1,

2, and 3, although energy auditing is actually more of a continuum as shown in the chart here.



Energy Audits: The cost of an energy audit depends on the time it requires and the complexity of the services offered. The customer’s commitment to energy conservation and the energy auditor’s capabilities determine the level of the energy audit and which services are rendered as part of the audit.

The Level 1 energy audit can be as simple as a paper form or internet survey. Or it may be a limited home visit to collect information and perform simple customer education. Level 2 energy audit usually includes a blower door test and may include computer modeling. Level 3 audits focus on diagnosing specific serious problems and prescribing solutions. The training level of the auditor determines what level of audit he or she is qualified to perform.

1.2.1 Screening and Surveys


Many energy conservation programs include screening, which is a preliminary evaluation of customer needs that requires less effort than more comprehensive audits. Screening methods include the internet-based energy audits that are completed by customers and customer phone calls that are processed for further analysis.

The goal of screening is to gather information by a less expensive method than sending a highly trained individual to do a comprehensive energy audit. Screening results in requests for further information, leads for energy contractors, and requests for additional energy-auditing services.

CHAPTER 2: EVALUATING INSULATION

Determining insulation levels, and estimating labor and materials for retrofit insulation, are among the energy auditor's most important tasks. The auditor should also determine how the crew will access the attic, crawl spaces, and other difficult locations, and, if necessary, obtain customer approval for this access.

This chapter focuses on the thermal resistance provided by insulation. It also addresses the construction details of building components which are commonly retrofitted with insulation.



Balloon Framing: Balloon framing is characteristic of some older homes. The wall cavities of balloon-framed houses are often open to both the basement and the attic.

Platform Framing: Modern homes on the other hand feature pre-built roof trusses, platform framing, and 4' x 8'-sheets of plywood or OSB sheathing material for walls, floors and ceilings.

2.1 INFRARED SCANNING

Use an infrared scanner, in conjunction with a blower door when possible, to view the wall from the interior or exterior of the home using the following general recommendations.

Try to scan on very hot or very cold days. The quality of definition and contrast of the view depends on the temperature difference between indoors and outdoors. Well-insulated walls have a sharp definition between the studs and insulated cavities. Uninsulated walls have a poorly defined difference between studs and cavity.



Infrared Scanner: Allows the user to see temperature differences which reveal the effectiveness of insulation and air-sealing details in building cavities.

View from indoors when possible because there are fewer solar effects such as warm spots in direct sun. However, viewing from outdoors can be effective at night during cloudy or very cold weather.

Evaluating IR-scanner images from outdoors requires experience with how different weather conditions and solar orientation affects the exterior temperatures of the building.

2.2 EVALUATING ATTIC OR ROOF INSULATION

Most attics and roof cavities have access hatches from inside the house. If there is no interior access, remove a roof vent, gable vent, or piece of soffit to look in the attic or roof cavity. If you choose to create a new interior hatch, cut in a closet at least 14 by 20 inches or as conditions permit. Get permission from the customer first.

- ✓ Try using a digital camera or a borescope held into a hole or cavity to aid your view of the insulation.


- ✓ Try using an IR scanner to find voids and irregularities in existing insulation.

If access to the attic isn't possible, estimate the attic insulation based on any information available, for example customer interview and insulation levels in similar building components. Be sure to note in your paperwork that this is an estimate only.

2.2.1 Attic Ventilation

Attic ventilation is intended to remove moisture from the attic during the heating season and/or to remove solar heat from the attic during the cooling season. It is often ineffective, however, and adding attic ventilation during insulation work is seldom necessary.

Many building codes require a minimum ratio of one square foot of net free area to 150 square feet of attic area. With a vapor barrier or with distributed ventilation (high and low), only one square foot per 300 square feet of attic area is required.



Low and High Attic Ventilation: Distributed ventilation — high and low — is more effective than vents that aren't distributed.

Adding attic ventilation won't cure a moisture problem caused by airborne moisture migrating up from the living space. Instead, preventing moisture from entering the attic is the best way to keep attic insulation dry. Ceilings should be thoroughly air-sealed to prevent moist indoor air from leaking through the ceiling.

Excess attic ventilation can drive ceiling air leakage through the stack effect, which can transport moisture from the house to the attic. Nighttime cooling of the roof deck can also cause water vapor that enters on ventilation air to condense on attic surfaces.

CHAPTER 3: *DIAGNOSING SHELL AND DUCT AIR LEAKAGE*

This chapter discusses how to diagnose air leakage through the building shell and through ducts. Buildings and their ducts vary widely in air-tightness, making testing and diagnosis an important part of modern energy auditing. Air leakage provides ventilation and combustion air in most homes and this makes diagnosis doubly important to ensure that good indoor air quality and safe combustion are a priority of weatherization and home performance work.

3.1 AIR-LEAKAGE PROBLEMS AND SOLUTIONS

The testing described here will help you analyze the existing air barriers and decide if air sealing is needed.

Ideally, an air barrier and insulation forms the thermal boundary, which completely surrounds a building. Leaks in the air barrier can cause the following deficiencies. Excessive air leakage is one of the typical home's biggest energy wasters.

- Air leakage can significantly reduce insulation R-value.
- Air leakage moves moisture and other pollutants into and out of the house.
- Air leakage can cause house pressures that can interfere with the venting of combustion appliances.

3.1.1 Driving Forces for Air Leakage


Building height and location, weather, and mechanical equipment all effect air leakage in a building.

Wind

Strong winds may create a positive pressure on one side of a building, and a negative pressure on another side.

Stack Effect

Air moves through a building as if it were a chimney. Depending on the outside temperature, air enters low or high in the building (infiltration) and exits at the top or bottom of the building (exfiltration). This is called the stack effect. The area between the air coming in at the bottom (infiltration) and the air leaving the building at the top (exfiltration) is called the neutral pressure plane.



Air Leakage Concepts: When performing air sealing, it helps to understand the effects of exhaust appliances, the stack effect, and wind effect.

Not much air leakage comes in or goes out near the neutral pressure plane. As the building is tightened at the bottom, the neutral pressure plane moves up. As the building is tightened at the top the neutral pressure plane moves down. For the best results, specify air-sealing at both the top and bottom of the building.

Duct Leakage Effects

Ideally, airtight return ducts gather air from the home, feed it to the air handler for heating or cooling, and airtight supply ducts supply the same air back to the home. Duct leaks are responsible for the following deficiencies.

- Duct leakage pressurizes the building, resulting in increased shell air leakage whenever the air handler is operating.

- Duct pressures can bring pollutants into the home and interfere with combustion-appliance venting.
- Unbalanced airflow between supply ducts and return ducts can pressurize and depressurize zones within the home. Recommend that operable supply vents be left open, or be replaced with non-operable grilles.

Exhaust Effects of Chimneys and Exhaust Fans

Chimneys and exhaust fans create negative pressure inside a home because they exhaust air from the home.

3.1.2 Safety Considerations for Air Sealing

Most homes depend on air leakage to provide outdoor air for ventilation. When air leakage provides ventilation, we evaluate the minimum ventilation requirement (MVR), which is the minimum amount of blower-door-measured air leakage that provides sufficient ventilation by air leakage. *“Evaluating Home Ventilation” on page 251*

Air sealing or duct sealing may affect combustion-appliance venting by changing house pressures or reducing the available supply of combustion air. After all weatherization measures have been performed, technicians must conduct worst-case testing of all combustion appliances. *See “Worst-Case Testing for Atmospheric Venting Systems” on page 129.*

3.1.3 Goals of Air-Leakage Testing

The first goal of air-leakage and pressure testing is to decide how much time and effort is required to achieve cost-effective air-leakage and duct-leakage rates, while safeguarding indoor air quality.

The second goal of leak testing is to decide where to locate the thermal boundary with its air barrier and insulation adjacent to one another. An intermediate zone like an attic or crawl space gives you two choices for completing the thermal boundary. The

CHAPTER 4: *EVALUATING HEATING AND COOLING SYSTEMS*

This chapter specifies energy efficiency improvements to heating and cooling systems.

The most important visual-inspection tasks are covered in this chapter. All heating systems should also be tested for combustion safety and steady state efficiency (SSE) as part of a comprehensive energy audit. Heating systems should be adjusted, repaired, or replaced, based on inspection and testing.

Cooling systems should be tested during service work for correct airflow and refrigerant charge. Decisions about air conditioning service or system replacement also depend on testing and visual inspection.

Duct leakage should be evaluated for both heating and cooling systems.

The inspection and testing procedures in this chapter may go beyond the auditor's training and daily practice. The reason they're included is that installation and service problems are common, and it makes sense for the auditor to be able to specify procedures for HVAC technicians. The better your quality control, the better energy savings, comfort, and customer satisfaction you can deliver. Consider the advanced procedures something to learn about as needed.


4.1 HEATING SYSTEM REPLACEMENT

Here, we discuss replacing furnaces and boilers. Water heaters are also discussed in this first section. Then we examine the fuel issues for both oil and natural gas.


4.1.1 Combustion Furnace Replacement

This section is for the air handlers of combustion furnaces. Successful furnace replacement requires selection of the right furnace and testing to verify that the new furnace is operating correctly.

- ✓ Make sure that the furnace is sized correctly, using an accurate methodology such as Manual J.
- ✓ Select a 90+ AFUE furnace and specify its installation as a sealed-combustion (direct vent) unit.
- ✓ Specify a programmable thermostat, if customers' schedule and behavior allows.
- ✓ Verify that all accessible ducts were sealed as part of installation, from the air handler and plenums to the branch connections.




Static Pressure and Temperature rise: Testing static pressure and temperature rise across the new furnace should verify that the duct system isn't restricted. The correct airflow, specified by the manufacturer, is necessary for high efficiency.



Sealed Combustion Heaters: Sealed combustion furnaces and boilers prevent the air pollution and house depressurization caused by some open-combustion heating units.

- ✓ If flue-gas temperature or supply air temperature are unusually high, check static pressure and fuel input. See *“Ducted Air Distribution”* on page 150.
- ✓ Filters should be held firmly in place and provide complete coverage of blower intake or return register. Filters should not permit air to bypass the filter when installed in the return plenum. Filters should be easy to replace.



90+ Gas Furnace: A 90+ furnace has a condensing heat exchanger and a stronger draft fan for pulling combustion gases through its more restrictive heat-exchange system and establishing a strong positive draft.

80+ Gas Furnace: An 80+ furnace has a restrictive heat exchanger, a draft fan, and has no draft diverter or standing pilot.

4.1.2 Combustion Boiler Replacement

Boilers are replaced as an energy conservation measure or for health and safety reasons. Boiler seasonal efficiency is more sensitive to proper sizing than is furnace efficiency.

CHAPTER 5: BASELOAD MEASURES

Baseload energy consumption—water heating, refrigeration, lighting, clothes drying, and plug loads—accounts for a large part of the energy use in most homes. In mild climates, baseload consumption may be larger than heating and cooling combined. Water heating, refrigerators, and lighting are discussed in this chapter.

5.1 WATER-HEATING ENERGY SAVINGS

The most important tasks in evaluating hot water energy savings are determining the water heater's insulation level, measuring the shower's flow rate, and measuring the hot-water's temperature.

5.1.1 Determining the Water Heater's Insulation Level

Common storage water heaters consist of a tank, insulation surrounding the tank, and an outer shell. There is typically either 1 or 2 inches of insulation surrounding the tank. The insulation is either fiberglass, if the water heater was manufactured before 1991, or polyisocyanurate if it was manufactured after 1991.


Follow this procedure to determine the water heater's insulation level.

- ✓ Look for a listing of R-value on a label on the water heater.
- ✓ Find a hole in the outer shell where the flue pipes emerges or where plumbing connects. Look around the hole for either fiberglass or polyisocyanurate insulation.
- ✓ If the hole isn't large enough, on an electric water heater, try the access panel for the heating element after disconnecting power from the unit.

- ✓ You may just be able to see the gap between the tank and outer shell. If you can't see this gap, use a ruler or probe to push through the insulation along side of a pipe connecting to the tank until the probe hits the steel tank to determine thickness. Make sure that the probe is against the tank and not against a nut welded to the tank.

Identifying Tank Insulation

Look here: gap around flue



- ✓ If the existing water heater has less than R-10 insulation, specify a water-heater blanket for the unit.

Table 5-1: Insulation R-Values

Insulation/thickness	R
Fiberglass 1 inch	3
Fiberglass 2 inches	6
Isocyanurate 1 inch	6.5
Isocyanurate 2 inches	13
Isocyanurate 3 inches	19.5

5.1.2 Water Heater Blankets

Install an insulation blanket on all heaters that are outside the heated space, unless the manufacturer's label prohibits it. Follow these guidelines to avoid fire hazards and to simplify future service.


Gas Water Heaters

- ✓ Keep insulation at least 2 inches away from the gas valve and the burner access panel. Do not install insulation below the burner access panel.
- ✓ Don't cover the pressure relief valve.

- ✓ Don't insulate the tops of gas- or oil-fired water heaters to avoid obstructing the draft diverter.

Electric Water Heaters

- ✓ Cut the blanket around the thermostat and heating element access plates, or cover the plates and mark their location on the insulation facing.
- ✓ Don't cover the pressure relief valve.
- ✓ Cover the top of the water heater with insulation if it doesn't obstruct the pressure relief valve.



Water Heater Insulation: Insulation should be installed carefully so it doesn't interfere with the burner, elements, draft diverter, or pressure relief valve.

5.1.3 Measuring and Adjusting Hot Water Temperature

- ✓ Measure the water heater's water temperature at the nearest faucet to the water heater, and reduce the temperature to 120° F with the customer's permission.

CHAPTER 6: *WINDOWS, DOORS, AND EXTERIOR INSULATION*

This chapter discusses these topics that relate to energy and repair measures.

- Window shading for low-cost cooling.
- Storm windows.
- Doubling of primary windows.
- Weatherstripping and repair of windows and doors.
- Window replacement.
- Window and door replacement with exterior insulation.

If windows and doors are in poor condition, their repair is often essential for a building's survival even if it's not an energy-saving measure. All tasks relating to window and door repair should be accomplished using lead-safe repair methods.

6.1 WINDOW SHADING

Much of the solar energy that strikes a home's windows passes through the glass and enters the living space. This solar heat accounts for up to 40% of summer overheating in many homes. It's better to block solar heat before it enters the home than to cool the home after the sun overheats it.

Window shading increases comfort and reduces the cost of cooling. Window shading is one of the most cost-effective weatherization measures in hot climates. Not all windows cause overheating, so you should direct your suggestions and specifications towards windows where the most solar heat enters.

- Windows that face east or west
- Windows that face south and have no effective roof overhang.


- Large windows.
- Skylights or other sloping glass.

6.1.1 Exterior Window Shading Treatments


Sun screens, made of mesh fabric, which is stretched over an aluminum frame, are one of the most effective window-shading options. They absorb or reflect a large portion of the solar energy that strikes them, while allowing a view through the window.

Sun screens are installed on the outside of the window, and work well on fixed, double-hung, or sliding windows. For casement and awning windows, the sun screen should be mounted on the movable window sash rather than on the window frame.

Awnings, exterior venetian blinds, and exterior rolling shades and shutters are also very effective but are more expensive than sun screens.



Sun Screen



Adjustable Awning



Exterior Venetian Blind

Exterior Shading: Installed on the window's exterior, these devices absorb or reflect solar heat before it enters the home. This strategy is superior to interior window treatments, which reflect heat back after it has entered.

6.1.2 Interior Window Shading Treatments

Interior shades or curtains are not as effective as exterior shades because they allow solar energy to enter the home. A significant portion of this heat remains inside the home.

Venetian blinds or opaque roller shades with bright white or metallic surfaces facing the exterior can block considerable solar heat.

Avoid translucent or light-admitting shades and blinds because they allow more heat to enter the home. Purchase window shades in the standard sizes that fit most windows since custom-sized shades are considerably more expensive.

Good management of window shades improves their effectiveness. Discuss these principles with the customers.

- ✓ Close window shades in the morning before the home begins to heat up. Also close the windows.
- ✓ Open shades in the evening to help cool the home. Also open the windows.
- ✓ Open south-facing shades all day during winter to allow solar heat to enter the home.

Metalized window films are applied to the inside of existing single- and double-pane windows. Non-metalized window films aren't appropriate for effective window shading. Highly reflective window films have shading coefficients as low as 0.30.

6.1.3 Landscaping for Shade

Trees and bushes can provide shade for windows, walls, and roofs. They also cool the air around the home with shade and moisture evaporating from their leaves. Well-planned landscaping can reduce an un-shaded home's air-conditioning costs by up to 50% while adding value to the home and neighborhood.

The best plan for cool landscaping includes tall deciduous trees on the south side of the home to block high mid-day sun. Shorter trees or bushes on the east and west block morning and afternoon sun.

Suggest planting deciduous trees that lose their leaves in the autumn to admit winter sun. Choose types that are quick-growing and easy to care for in your region. Advise customers to

CHAPTER 7: HEALTH AND SAFETY

This chapter introduces some of the most pressing hazards that customers face in their homes. Major hazards and potentially life-threatening conditions should be corrected before installers begin work in the dwelling unless the installers are making the corrections as part of their work. Among the most important pollutants are air pollutants. Source control is the best strategy for reducing indoor air pollution. In airtight homes, whole house ventilation systems are necessary to assure good indoor air quality.

7.1 POLLUTANT SOURCE CONTROL

The control of pollutants such as moisture and volatile organic compounds becomes more important as homes become more airtight.

Controlling pollutants at the source is always the best solution, especially in tighter homes. Mechanical ventilation can help remove and dilute pollutants, but ventilation isn't the first choice for pollutant control.


Auditors should survey the home for pollutants before weatherization or home performance work and to specify the following measures if needed.

- ✓ Repair roofs and plumbing leaks.
- ✓ Install a ground-moisture barrier over any bare soil in crawl spaces or basements.
- ✓ Vent clothes dryers and exhaust fans directly to the outdoors and not to attics or crawl spaces.
- ✓ Confirm that combustion-appliance vent systems operate properly.
- ✓ Replace unvented space heaters with vented appliances.

The home's occupants have control over the introduction and spread of many home pollutants. Educate residents about minimizing pollutants in their homes.

7.1.1 Carbon Monoxide (CO)

The EPA's suggested maximum 8-hour exposure is 9 ppm in room air. CO at or above 9 ppm is often linked to malfunctioning combustion appliances within the living space, although cigarette smoking or automobile exhaust are also common CO sources.



Causes of Carbon Monoxide

CO is often linked to unvented gas space heaters, kerosene space heaters, backdrafting vented space heaters, gas ranges, leaky wood stoves, and motor vehicles idling in attached garages or near the home. Central furnaces and boilers that backdraft may also lead to high levels of CO.

Effects of CO: This graph's 6 curves represent different exposure levels in parts per million.

CO is normally tested near the flame or at the exhaust port of the heat exchanger. CO is usually caused by one of the following.

- ✓ Gas appliances that are overfired for their rated input.
- ✓ Backdrafting of combustion gases smothering the flame.
- ✓ Flame interference by an object (a pan over a gas burner on a range top, for example).
- ✓ Inadequate combustion air.
- ✓ Flame interference by rapidly moving air.
- ✓ Misalignment of the burner.

- ✓ Blockage in the flue or heat exchanger.

Appliance service technicians should strive to identify and correct these problems.


Testing for Carbon Monoxide

The most common CO-testing instruments are electronic sensors with a digital readout in parts per million (ppm). Follow the manufacturer's recommendations on zeroing the meter – usually by exposing the meter to clean air. CO testing equipment usually needs to be re-calibrated every 6 months or so, using factory-specified procedures.

7.1.2 Gas Range and Oven Safety

Test gas ranges and ovens after all other vented appliances have been tested. Range top burners must be tested as measured (in ambient air without adjustment for oxygen content). Follow this procedure.

1. Remove all pots and foil from the burner area.
2. Turn each range top burner on high and allow to warm.
3. Test burner combustion gases 6 inches above the flame.
4. Test the oven with the probe inside the oven vent.




CO from Range and Oven: Measure CO at burners from 6" away. Measure CO at oven in undiluted flue gases.

Note: To protect both yourself and the customer, continually monitor ambient space around oven during testing. The ambient air should not exceed 9ppm for any 8-hour period.

CHAPTER 8: *EVALUATING MOBILE HOMES*

Mobile homes typically use more energy per square foot than site-built homes, but their consistent construction makes them more straightforward to weatherize. Insulation upgrades save the most energy in mobile homes, though sealing shell and duct air leaks are also excellent energy-saving opportunities. Mobile home heating-system replacement are often cost-effective when a customer's energy usage is high.



Typical Components of a Mobile Home: 1–Steel chassis. 2–Steel outriggers and cross members. 3–Underbelly. 4–Fiberglass insulation. 5–Floor joists. 6–Heating/air conditioning duct. 7–Decking. 8–Floor covering. 9–Top plate. 10–Interior paneling. 11–Bottom plate. 12–Fiberglass insulation. 13–Metal siding. 14–Ceiling board. 15–Bowstring trusses. 16–Fiberglass insulation. 17–Vapor barrier. 18–Galvanized steel one-piece roof. 19–Metal windows.

8.1 MOBILE HOME GENERAL AUDITING TASKS

Explain to the customer that you need access to all areas of the home including bedrooms, bathrooms, and closets.

Ask customers if they notice problems with the furnace, water heater, or any problems in the building shell.

Advise the customer that inspection holes may need to be drilled in inconspicuous locations in their home for auditing and inspection purposes.

Explain the general procedure of the audit and the weatherization process including the blower door test, health and safety tests, and inspection of insulation levels.

8.1.1 Health and Safety

Consider the following important health and safety issues, which are connected to mobile home weatherization.

- ✓ Check the furnace for cracks in the heat exchanger, gas leaks, carbon monoxide, flex connector, and venting.
- ✓ Check the water heater for carbon monoxide, spillage, venting, gas leaks, and adequate combustion air.
- ✓ Open-combustion furnaces and water heaters located in the living space should be replaced because open-combustion appliances are illegal and unsafe for mobile homes. New furnaces and water heaters must be sealed-combustion units, labeled and approved for mobile or manufactured homes.
- ✓ Check gas range and dryer gas line flex connector.
- ✓ Check dryer (gas or electric) for proper venting to outdoors.
- ✓ Look for rot in the rim joist and bottom of the wall.
- ✓ Look for signs that the home may not be level, such as window and door frames not being square.

- ✓ Check for mold and mildew especially at the bath and kitchen areas.
- ✓ Check for moisture problems that could degrade weatherization measures, such as plumbing leaks and roof leaks.

See “*Health and Safety*” on page 239.

8.1.2 Repair Work

Repairs are measures necessary for the effective performance or preservation of weatherization installations. Specify cost-effective repairs to the ceiling, sidewall and belly as necessary to prepare for retrofit insulation. Repairs are necessary to seal large air leaks. Repairs may also be necessary to solve health and safety problems. You may specify the following necessary repairs.

- ✓ Roof leaks and repairs.
- ✓ Moisture and drainage repairs.
- ✓ Ceiling panel repair and or replacement.
- ✓ Belly repairs.
- ✓ Plumbing supply leaks. Focus on hot water leaks that also waste fuel.
- ✓ Repair sewage leaks that present a health hazard.
- ✓ Ductwork repairs.
- ✓ Other structural repairs such as repairing rotted floors and walls.
- ✓ Repairing or replacing windows.
- ✓ Home re-leveling

APPENDICES

A-1 REQUIRED DIAGNOSTIC EQUIPMENT

Minimum Equipment For Instrumented Air Sealing

- ✓ Fully instrumented and calibrated blower door, Minneapolis Model 3 or equivalent, capable of measuring CFM₅₀ (Cubic feet per minute at 50 Pascals).
- ✓ DG-3 or DG-700 handheld Digital Manometer, or equivalent.
- ✓ Smoke generating equipment.

Minimum Equipment for Heating System Analysis

- ✓ Combustion analyzer.
- ✓ CO testing capacity.
- ✓ Draft gauge or manometer.
- ✓ Heat exchanger leakage testing equipment.
- ✓ Ammeter (sensitive enough to adjust thermostat anticipators).
- ✓ Gas leak detector.

A-2 R-VALUES FOR COMMON MATERIALS

Material	R-value
Fiberglass or rock wool batts and blown 1"	2.8–4.0
Blown cellulose 1"	3.0–4.0
Vermiculite loose fill 1"	2.7
Perlite 1"	2.4
White expanded polystyrene foam (beadboard) 1"	3.9–4.3
Polyurethane/polyisocyanurate foam 1"	6.2–7.0
Extruded polystyrene 1"	5.0
Sprayed 2-part polyurethane foam 1"	5.8–6.6
Icnene foam 1"	3.6
Oriented strand board (OSB) or plywood 1/2"	1.6
Concrete or stucco 1"	0.1
Wood 1"	1.0
Carpet/pad 1/2"	2.0
Wood siding 3/8–3/4"	0.6–1.0
Concrete block 8"	1.1
Asphalt shingles	0.44
Fired clay bricks 1"	0.1–0.4
Gypsum or plasterboard 1/2"	0.4
Single pane glass 1/8"	0.9
Low-e insulated glass (Varies according to Solar Heat Gain Coefficient (SHGC) rating.)	3.3–4.2
Triple glazed glass with 2 low-e coatings	8.3

A-3 CALCULATING ATTIC INSULATION

Auditors and inspectors also help crews determine how much insulation is needed for ceilings and walls.

Calculating Attic Loose-Fill Insulation

Loose-fill attic insulation should be installed to a uniform depth to attain proper coverage (bags per square foot) so it attains the desired R-value at the settled thickness. Follow the manufacturer's labeling in order to achieve the correct density to meet the required R-value. Attic insulation always settles: cellulose settles between 10% to 20% and fiberglass settles between 3% to 10%. For this reason, it's best to calculate insulation density in square feet per bag rather than installed thickness.

TABLES AND ILLUSTRATIONS

Energy Audits and Customer Relations

Energy Audits	17
Auditor’s Floor Plans.....	19
Visualization.....	19
Interior and Exterior Inspection	20
Seasonal vs. Baseload Domination of Energy Use	25
Top Six Energy Uses for U.S. Households	27
Separating Baseload from Seasonal Energy Use.....	28
Total Energy Use and the HERS Index.....	29
The Summer Peak	31
Range of Electric Baseload Consumption	32
Carbon Emissions of Various Fuels	33
Modern Dryer Dials	43
Clothes Line.....	43
Circulating Fans	45
Ventilating Fans	45

Evaluating Insulation

Balloon Framing.....	47
Platform Framing.....	47
Infrared Scanner.....	48
Low and High Attic Ventilation.....	49
Finished Attic.....	51
Finished Attic Best Practices	52
Foam-Insulated Kneewall	52
Insulating Closed Roof Cavities.....	53
Insulating and Sealing Attic Stair Walls, Doors, and Stairs.	54
Insulating and Weatherstripping the Attic Hatch.....	54
Stairway Hatch Dam	55

Manufactured Retractable-Stair Cover.....	55
Story-and-a-Half.....	57
Thermal Boundary Decisions.....	58
Locating Foundation Air Barrier and Insulation	60

Diagnosing Shell and Duct Air Leakage

Air Leakage Concepts.....	62
Questions to Ask and Answer Before Air Sealing	64
Blower Door Components	66
Blower Door Test	67
Digital Manometer	67
Floor-Wall Junction.....	73
Finished Attic.....	74
Recessed Light Fixtures	74
Balloon-Framed Gable Wall	75
Two-Level Attic.....	75
Bypasses Under Bathtub.....	76
Exterior Walls & Stairs.....	76
Cathedral Ceiling with Recessed Light.....	77
Porch Air Leakage	77
Interior Door Test.....	80
Bedroom Test	81
Building Components and Their Air Permeance	82
Pressure-Testing Building Zones	83
House-to-Attic Pressure.....	84
Attic-to-Outdoors Pressure	84
Zone Connectedness	85
Cantilevered Floor Test	85
Porch Roof Test.....	85
Add-a-Hole Test 1	87
Add-a-Hole Test 2	87
Add-a-Hole Leakage Factors	88

Open-a-Door Test 1.....	90
Open-a-Door Test 2.....	90
Open-a-Door Leakage Factors	91
Pressure Measurements and Air-Barrier Location	93
House-to-Crawl-Space Pressure	94

Evaluating Heating and Cooling Systems

Sealed Combustion Heaters.....	96
Static Pressure and Temperature rise.....	96
90+ Gas Furnace.....	97
80+ Gas Furnace.....	97
Radiator Temperature Control	98
Simple Reverse-Return Hot-Water System	99
Reset Controller	100
Oil Heating System	101
Sealed Combustion Space Heater	102
Space Heater Controls	102
Atmospheric, Open-Combustion Gas Burners	104
70+ Furnace.....	105
80+ Furnace.....	105
Gas-Furnace Output from Temperature Rise and Airflow (1000s Btuh).....	108
Action Levels for Open-Combustion Gas Appliances	109
Combustion Standards for Gas Furnaces	110
Carbon Monoxide Causes and Solutions.....	111
Combustion Problems and Possible Solutions	111
Primary Air Adjustment.....	112
Input in Thousands of Btu/hr for 1000 Btu/cu. ft. Gas....	114
Clocking the Meter	115
Measuring Draft	117

Barometric Draft Control.....	119
Minimum Oil-Burner Combustion Standards	120
Typical Safe Draft for Oil-Fired Appliances	121
Measuring Oil-Burner Performance.....	122
Wood-Stove Installation	126
Guide to Venting Standards.....	127
Testing Requirements for Combustion Appliances and Venting Systems.....	129
Flame Roll-Out	130
Worst-Case Depressurization.....	131
Negative Versus Positive Draft	132
Maximum CAZ or Mechanical Room Depressurization for Various Appliances	133
Draft Problems and Solutions	135
Areas of Round Vents	137
Two Vent Connectors Joining Chimney.....	138
Connector Diameter vs. Maximum Horizontal Length...	138
Clearances to Combustibles for Vent Connectors	139
Masonry Chimneys	139
Clearances to Combustibles for Common Chimneys	140
All-Fuel Metal Chimney	141
Chimney Terminations.....	142
Roof Slope and B-Vent Chimney Height (ft).....	142
Flexible Metal Chimney Liners	143
AGA Venting Categories	144
B-Vent Chimney Liner.....	145
Characteristics of Gas Furnaces and Boilers	146
Passive Combustion-Air Options	148
Combustion Air Openings: Location and Size	149
Recommended Cross-Sectional Area of Metal Supply and Return Ducts at Air Handler	152
Round-Duct Square-Inch Equivalency for Metal Ducts ..	152

Airflow and Climate.....	153
Fan Curves	154
Furnace Operating Parameters.....	156
Adjustable Drive Pulley	157
A Fan/Limit Control.....	157
Pressure in Two Measurement Systems	158
Duct Blower Mounted to Air Handler.....	159
Static Pressure Probe	159
Duct Blower Mounted to Main Return.....	160
True Flow® Meter.....	163
Measuring Return Air with a Flow Hood	164
Visualizing TESP	165
Total external static pressure (TESP).....	167
Total External Static Pressure Versus System Airflow for a Particular System	167
Depressurized Central Zone.....	168
Pressurized Bedrooms	168
Furnace Filter Location	169
Restricted Return Air.....	171
Finding Duct Air Leaks.....	172
A Pressure Pan	173
Pressure-Pan Test.....	175
Problem Return Register.....	175
Dominant Return Leaks.....	176
Dominant Supply Leaks.....	176
Duct Leakage Standards	177
Total Duct Air Leakage Standards for Homes	178
Testing Ducts Before Air-Handler Installation	178
Total Duct Air Leakage Measured by the Duct Blower... ..	180
Measuring Duct Leakage to Outdoors.....	181
Panned Floor Joists.....	183
Flexduct Joints	184

Plenums, Poorly Sealed to Air Handler.....	184
Sectioned Elbows.....	184
Duct Insulation.....	185
Cast-Iron Sectional Boilers.....	186
Expansion Tank, Air Separator, and Vent.....	189
Zone Valves.....	189
Purging Air.....	190
One-Pipe and Two-Pipe Steam Systems.....	191
Two-Pipe Steam Systems.....	191
Steam Traps.....	193
Inside a Programmable Thermostat.....	194
Electric Baseboard.....	196
Electric Furnace.....	196
Is Strip Heat Activated?.....	197
Heat Pump.....	198
Compiled Research Results on HVAC Performance.....	201
Air-Conditioner Sizing.....	203
Charge-Checking.....	204

Baseload Measures

Insulation R-Values.....	206
Water Heater Insulation.....	207
Setting Hot-Water Temperature.....	208
Water-Saving Shower Heads.....	209
Measuring Shower Flow Rate.....	210
Standard Gas Water Heater.....	211
Fan-Assisted Water Heater.....	212
Sealed-Combustion Water Heater.....	212
Sealed-Combustion Tankless Water Heater.....	214
Obsolete Tankless Water Heater.....	214
Closed Loop Antifreeze System.....	216
Drainback System.....	216

Recording Watthour Meter.....	218
Refrigerator Consumption Example	219
Compact Fluorescent Lamps.....	221

Windows, Doors, and Exterior Insulation

Exterior Shading.....	224
Trees for Shade.....	226
Exterior Sliding Storm Windows.....	226
Clip-on Storm Window	226
Doubling Windows.....	227
Weatherstripping Double-Hung Windows.....	229
Weatherstripping Doors	230
Minor Door Repair.....	230
Threshold and Door Bottom	230
NFRC label	232
Replacement Window and Sill Angle	233
Flashing a Flanged Window.....	234
Safety Glass Around Doors.....	236
Windows Near Walking Surfaces	236
Fire Egress Windows.....	236
Exterior Foam Insulation.....	237

Health and Safety

Effects of CO	240
CO from Range and Oven.....	241
Advanced 4-Speed Range Fan	242
Moisture Sources.....	245
Moisture Sources and Their Potential Contributions	246
Dust Mites.....	247
Well Sealed Crawl Spaces	248
Knob-and-Tube Wiring	250

Finding the N-Value	254
Fan Sizes for Homes with Average Air Leakage	255
Multi-Port Exhaust Ventilation	257
Specifying Exhaust Fans	258
Fan Capacity, Maximum Noise Rating, & Efficacy.....	259
Supply Ventilation.....	259
Centralized Balanced Ventilation.....	260
Heat-Recovery Ventilator	261

Evaluating Mobile Homes

Typical Components of a Mobile Home.....	263
Bowstring Roof Details.....	266
Wall/Roof Details on Newer Homes	266
Bowstring Roof Cavity	266
Standard Mobile Home Construction.....	269
Older Mobile Home Construction	269
Checking Walls	270
Mobile Home Ducts	271
Floor Return Air	272
Air-Leak Locations and Typical CFM ₅₀ Reductions	275
Glass Interior Storms.....	276
Plastic Storms	276
Mobile-Home Double Window.....	277
Mobile-Home Double Door	278
Mobile-Home Door.....	278

Appendices

Typical Table from Insulation Bag	282
Insulation Coverage Table	282

INDEX

A

Add-a-hole test	85-86
Air barriers	
add-a-hole test	85-86
air permeance of	82
definition	79
primary vs. secondary	79
testing for leaks	77-86
testing with manometers	82-86
Air conditioners	
inspections	201-203
sizing	203
Air conditioning	
reducing costs of	43-44
refrigerant charge	204
Air filters	
oil burner	123
Air handlers	
See also Blowers	
sealing holes in	96
Air leakage	
concepts	62
effect	62
goals of testing	63-64
mobile homes	274-275
of materials, rates	82
sealing	73-77
when to test	66
Air permeance	
of building materials	82
Air quality. See Indoor air quality	
Air sealing	73-77
Air separator	189
Air shutters, oil	122
Airflow	
and climate	153
blower speed	153
dry & wet climates	153
improving low	169

measuring	151-164
studies	151
testing for unbalanced	167-168
troubleshooting	164-168
Air-to-air heat exchangers	260-261
Alarms	
carbon monoxide	243
smoke	242
American Gas Association	
venting categories	144
Annual Fuel Utilization Efficiency (AFUE)	144
Appliances	
energy measures	205-209
Asphalt felt	232
Attics	
hatches	77
insulation	48-53
ventilation	49-50
Automatic fill valve	190
Awnings	224

B

Backdrafting	126-130
Barometric dampers	119
Baseload	
analysis example	28
measures	205-210
Basements	
thermal boundary	59-60, 94
Blinds	
exterior	224
Venetian	224
Blower doors	
airtightness limits	253-256
components/description	66-68
preparing for tests	68-69
pressure diagnostics	77-86
simple zone testing	80-81

test procedures	70	Chimneys	139-142
testing	66-79	all-fuel	141
testing air barriers	82-86	clearances	140
Blowers		house-pressure effect	63
controls	155	masonry specifications	139
Boilers		measures to improve draft	134
corrosion	186	retrofit liners	142, 145
efficiency	189-190	termination	141
low-limit control	189	types	139
maintaining	42	when to reline	144
maintenance/efficiency	186-187	Client relations	264
sizing	97	Clothes dryers	
Building tightness limit.		efficient use	43
See Minimum ventilation level		Clotheslines	43
Building tightness limits	252, 253, 253-256	CO. See Carbon monoxide	
Burners		Coils	
gas, servicing	127-128	cleaning	201
nozzle for oil	122	Combustion	
oil	118-123	oil standards	109, 120
Bypasses	73-77	problems/solutions	111
C		testing/analysis	105-123
		the chemical process	104
		Combustion air	146-149
Cad cell	121	cfm requirements	130, 146
Carbon emissions		confined spaces	147-148
per unit of energy	33	methods of providing	146
Carbon monoxide	240	unconfined spaces	147
alarms	243	Combustion losses	
causes of	240	excess air	189
causes/solutions	111	Combustion testing	
exposure limits	241	drilling holes	110
standard for oil	110, 120	Combustion zone	
testing	129, 241	definition	130, 146
CAZ	148	Comfort	
CFL. See Compact fluorescent lamps		staying cool	43-44
CFM50		Compact fluorescent lamps	220-221
defined	66	Concrete vapor-proofing	249
Charge		Condenser coils	
refrigerant	204	cleaning	201
Chimney liners		Conditioned space	
insulating	143	definition of	57
sizing	143	versus unconditioned	58

Consumption	
of energy	24
Contracts	34
Convectors	
fin-tube	190
Cooling	
energy saving tips	43-44
with fans	43
Corrosion	186
Costs	
measure selection	25
seasonal/baseload	26
Crawl spaces	
thermal boundary	59-60, 94
Customer education	40-44
Customer relations	15-38

D

Dampers	
balancing	155
Diagnostics	
airflow	164-168
building shell	77-84
equipment for	279
house pressure	176-177
pressure-pan testing	173-175
unbalanced airflow	167-168
Doors	228-229
bottoms and sweeps	229
mobile home	278
repair	228-229
repairing	228
replacement	
mobile homes	278
weatherstrip	228-229
Draft	
and duct improvements	134
measuring, illus.	117
over-fire	120
strength & types of	129-130
Duct blower	
leak-testing	178-181
measuring airflow	158-161

Ductboard	
deteriorating facing	183
Duct-induced house pressure	
176-177	
Ducts	150-155, 171-185
design airflow	151-153
duct-airtightness testing	178-181
evaluating leakage	171-175
finding leaks	172-175
hangers	182
house-pressure effect	62
improvements to solve draft	
problems	134
leakage standards	178
measuring airflow	158-164
mobile homes	270-274
pressure-pan testing	173-175
sealing boots and registers	76
sealing chases	76
sealing leaks	181-183
sizing	151-152
static pressure	164-166
troubleshooting leakage	172-183
Dust	
lead	249

E-F

Education	
customer	40-44
Efflorescence	247
Electric heat	194-200
baseboard	195-196
furnaces	196
Electrical safety	250
Energy	
baseload measures	205-210
consumption	24
Energy audit	
ethics, bias	37
health and safety	22
interior/exterior inspection	18-20
mechanical inspection	20-21

Energy auditor responsibilities	15-38
Energy audits	
ethics, bias	37
Energy factor	
water heating	212
Energy recovery ventilators	260-261
Energy use	
analysis	24-28
analysis, example	28
Ethics	15-38
Excess air	
oil burners	120
Exfiltration	
See also Air leakage	
concepts	62
Expansion tanks	188, 189
Fan curves	154
Fans	
for cooling	43
Filters	202
air, installation	97
changing	41
Flexduct	
joints	182
Flow hood	163
Flue dampers. See vent dampers	
Flue-gas analysis	119
Fluorescent lamps	
compact	220
Furnaces	150-185
installation	96-97
mobile homes	270
operating parameters	156
replacement	96-97
sealing holes in	96
temperature rise	155

G

Gas burners	
clocking gas meter	113
operation of	104

Gores	182
Grilles	
cleaning	41
Ground moisture barrier	60, 249

H

Health and safety	
inspection	22
mobile homes	264-265
Heat pumps	
efficiency	197-198
room	199-200
testing	198
Heat recovery ventilators	260-261
Heating systems	
electric	194-200
electric baseboard	195-196
electric furnaces	196
forced-air	150-185
heat pumps	197-198
hot-water	186
hydronic	97-100, 187-190
oil-fired	118-123
replacement	100
room heat pumps	199-200
steam	190-193
High limit	
hot-water heating	188
steam	192
House pressures	
limits	168
measuring	67
problems with	63
reducing	134
unbalanced airflow	167-168
HRVs.	
See Heat recovery ventilators	

Hydronic heating systems 187-190

I

IAQ. See indoor air quality

Indoor air pollution

controlling 239-241

Indoor air quality 240-241, 253-256

Infiltration

concepts 62

Inspections

air conditioners 201-203

final 35

health and safety 22

in-progress 35

interior/exterior 18-20

mechanical systems 20-21

wall insulation 55

Insulation

accessing walls 55

attic 48-53

coverage, mobile home 266-269

exterior 237

floor, mobile home 267-268

hydronic pipe 99

hydronic piping 190, 193

mobile home 266-269

roof, mobile home 266-267

steam piping 190, 193

wall, mobile home 269

water heaters 205-207

Intermediate zones

definition 58

J-M

Kneewalls 74

Landscaping

for shade 225

Laundry

energy savings in 43

Lead paint 249

Lead-safe weatherization 249

Leakage area 72

Lighting 220-221

recessed 76

Line-voltage thermostats 195

Low-flow shower head 209

Low-limit 99

Manometer 160, 162, 163

digital 67

Manometers

digital 130

hose connections 67

Mesh tape 182

Metering

refrigerators 217-219

Mildew 247

Minimum ventilation level 65

Mobile homes 263-278

air leakage 274-275

auditing 264

belly insulation 267-268

construction/components 263

door replacement 278

ducts 270-274

furnaces 270

health and safety 264-265

insulation 266-269

insulation coverage 266-269

repairs 265

roof insulation 266-267

storm windows 276

wall insulation 269

water heaters 275-276

windows 276-277

windows/doors 276-278

Moisture

and health 246

barriers, ground 60, 249

sources 244-246

Mold 247

N-O

National Fire Protection Association
standards 126

Natural gas
heat content 115
leak testing 113

Neutral pressure plane 62

NFPA. See National Fire Protection Association

Oil burners 118-123
air filter 123
excess air 120
ignition 119
maintenance/adjustment 122-123
nozzles 122
performance indicators 110, 120

Oil filters 123

Oil pressure 110, 120

Outdoor thermostat 199

Over-fire draft 120

P-Q

Paint
failure 247
lead 249

Pipe insulation 190, 193
DHW 208-209

Plumbing penetrations
sealing around 75

Pollution
controlling sources 239-241

Porch roof
testing air leakage through 85

Power venters 145

Pressure
measuring differences in 67
pan testing 173-175
pascals/IWC conversion 158

See also House pressures

WRT notation 67

zone leak-testing 82-84

Pressure boundary
See also Air barrier, Insulation

Pressure pan testing 173-175

Pressure tank 98
and pump 98

Pressure-relief valve 98, 188

Primary air
adjustment 112

Programmable thermostats 195

Propane 144
finding leaks 128

Pumps
hydronic, installation 98

Quality assurance 36

Quality control 36

R-S

Radiators 190

Recessed lights 74

Refrigerant
charge 204

Refrigerators
evaluation and replacement 216-219
metering 217-219

Registers
opening 41

Repair
doors 228-229
windows 228

Repairs
mobile homes 265

Reset controllers 190

Rough opening 234

R-values
determining 47-55

Safety
electrical 250

Shade trees	225	Thermostats	
Siding		cooling settings	44
replacement	237	heating settings	41
Sizing		line voltage	195
air conditioners	203	outdoor	199
Smoke alarms	242	programmable	195
Smoke number	120	two-stage	199
Soffits		Torchiere	220-221
kitchen	74	TrueFlow®	161
Solar heat-gain coefficient	232	Tyvek	232
Stack effect	62	U-factors	
Static pressure	164-166	determining	47-55
Steady-state efficiency	110, 120	window	232
testing for	119	Unconditioned spaces	
Steam heating	190-193	definition of	57
Steam traps	191, 193	Utility bills	
Stick pins	185	analysis, example	28
Storm windows	226	Vapor-proofing	
Subcooling	204	concrete	249
Sun screens	224	Venetian blinds	224
Superheat	204	Vent connectors	136-138
Superheat test	200-201	clearances	139
Supply ventilation	259	materials	136
		specifications	137
T-V		Vent dampers	190, 191
<hr/>			
Tape		Ventilation	
holding power	183	attic	49-50
Temperature rise		balanced	259-260
furnace	110, 155	determining need for	252
The Energy Conservatory	161	exhaust	257-258
Thermal boundary		supply	259
See also Air barrier		systems	257-261
basements and crawl spaces		whole house	257-261
59-60, 94		Venting	
definition	57	See also Ventilation	
ideal location	93	AGA categories	144
Thermal bypasses		atmospheric	126-143
locations of	73-77	fan-assisted	144
sealing	73-77	W-Z	
Thermal resistance		<hr/>	
calculating	47-55	Water heaters	
of insulation materials	280	draining sediment	43
		efficient use	43

energy efficiency	205-208	simple pressure test	81
insulation	205-207		
pipe insulation	208-209		
replacement	210-212		
mobile homes	275-276		
sealed-combustion	212		
setting temperature	207		
Water temperature			
setting	207		
Weather-resistant barrier	231, 232		
Weatherstrip			
attic hatches	77		
doors	228-229		
windows	228		
Wind	62		
Windows	223-237		
doubling	227		
exterior treatments	224		
measuring	234, 235		
mobile home	276-277		
repair	228		
replacement	231-237		
safety	235-236		
shade trees	225		
shading	223-225		
storm	226		
waterproofing	233		
weatherstrip	228		
Windows/doors			
mobile homes	276-278		
Wood decay	247		
Wood heating	123-126		
clearances	123		
inspection checklist	125		
Wood stoves			
UL-listed	123		
Work orders	33-34		
Worst-case draft test	129-130		
Zones			
combustion-appliance	130		
input vs. reference	67		
intermediate	171		
pressure testing	82-86		